

850 Series

Generation 6 *MX* Detection Range



Features

- // Optical Smoke, Heat, or Multi-Sensor detectors
- // Enhanced chamber design
- // Extended drift compensation
- // Built-in short circuit *MX* loop isolator
- // Range of colour options
- // Remote programming via Infrared link
- // AS 7240.5 Listing (heat detectors)
- // AS 7240.7 Listing (smoke detectors)



Advanced Fire Detection Technology

The Generation 6 850 Series fire detectors are designed to be both adaptable and flexible, which means they can be used in most premises to protect against a wide range of potential fire risks. They use sophisticated digital signalling to communicate with the *MX TECHNOLOGY* fire control panel. A range of standard and functional bases variously protect against short circuits, moisture ingress, and provide output control and sounder functions.

The ability of the 850EMT Engineering Management Tool to interrogate and program detectors connected to a VIGILANT *MX1* system via a 2-way infrared link, together with a range of bases and accessories, helps make the 850 Series detectors safe, quick, and easy to install.

The Ceiling Tile adaptor (CTA) allows detectors to be pre-commissioned and tested before the suspended ceiling is fitted.

Standard and custom colour options allow the detectors to either blend into the décor or be easily located against a contrasting background.

MX Gen6 Detector Features

- Choice of heat, smoke or heat/smoke multi-sensor
- Advanced multi-sensor designs
- Enhanced immunity to false activation
- Up to 250 devices per *MX* loop
- Built-in short circuit line isolator
- Quick and easy to install
- Two-way infrared programming with 850EMT
- Dual colour indication for Alarm and Isolator operation
- Comprehensive range of bases and base accessories
- Compatible with Ceiling Tile Adaptor (CTA) Time-Saver Mount
- Cover and base available in any Pantone colour



850PH Multi-Sensor Smoke and Heat Detector



With the ability to detect a wide range of fires from flaming to smouldering types, the combined optical and heat multi-sensor detector is the preferred choice for a range of applications including light industrial, retail and office environments. It operates in a number of modes and sensitivities that can be selected to suit different environmental conditions.

The heat sensor can generate a separate alarm using the A2S fixed temperature mode or the A2R rate-of-rise and fixed temperature mode.

All the 850 Series detectors feature a built-in short-circuit line isolator which is active when the detector is used with a 4B-C base. Providing peace of mind and reducing the overall system cost.

Technical Specifications

Operating Voltage	20 to 40Vdc
Quiescent Current	330µA (typ.)
Ambient Temp.	-25 °C to +70 °C
Relative Humidity	10% to 95% (non-cond)
Dimensions	109 dia x 43H mm
Weight	76g
ActivFire Listed	afp-2930
FPANZ Listed	Pending

Part Number 516.850.051.E

850H Heat Detector



To complement the range the heat sensor can operate in fixed temperature or combined fixed temperature and rate-of-rise modes A2S, A2R, CS and CR. It is often used in areas where high levels of dust are present or where the environment precludes the use of smoke detectors.

All the 850 Series detectors feature an LED indicator which changes colour depending on the detector's state. With the system normal, the LED flashes red every 5 seconds when it is polled by the VIGILANT panel. Should a short-circuit occur, the LED will show yellow. If the detector is in alarm, the LED will show red. The detector's LED flashes yellow to indicate communication via IR with the 850EMT.

Technical Specifications

Operating Voltage	20 to 40Vdc
Quiescent Current	290µA (typ.)
Ambient Temp.	-25 °C to +70 °C
Relative Humidity	10% to 95% (non-cond.)
Dimensions	109 dia x 43H mm
Weight	81g
ActivFire Listed	afp-2927
FPANZ Listed	Pending

Part Number 516.850.053.E

850P Smoke Detector



More benign environments where any potential fire will be slow burning can be protected using the optical detector. A choice of sensitivities and modes gives this detector a broad range of applications.

All the 850 Series detectors have the capability to communicate with the 850EMT service tool via a bidirectional infrared link when connected to a VIGILANT *MX7* panel. This enables the detectors to be interrogated and programmed from the ground. No ladder required.

In IR mode, the detector's LED flashes yellow to indicate when an IR link is established between it and the 850EMT.

Technical Specifications

Operating Voltage	20 to 40Vdc
Quiescent Current	330µA (typ.)
Ambient Temp.	-25 °C to +70 °C
Relative Humidity	10% to 95% (non-cond)
Dimensions	109 dia x 43H mm
Weight	76g
ActivFire Listed	afp-2928
FPANZ Listed	Pending

Part Number 516.850.052.E

801F Flame Detector



The 801F point type flame detector presents a cost-effective solution to providing high reliability flame detection for indoor applications. The 801F is a full featured flame detector for indoor use and boasts a high degree of false alarm immunity. The 801F is designed for direct connection to the *MX* digital loop, employing the same universal detector base or functional base as the 850 series fire detectors. An intrinsically safe version is also available.

Technical Specifications

Operating Voltage	20 to 40Vdc
Quiescent Current	300µA (typ.)
Range 1	0.4m2 n-heptane at 50m
Field of View	100o
Ambient Temp.	-20°C to +70°C
Relative Humidity	10% to 95% (non-cond)
Dimensions	109 dia x 22H mm
Weight	110g
FPANZ Listed	VF/354
Part Number	516.800.006

1. Distance measured on axis

SAB801 Sounder Addressing Beacon & SAM800 Sounder Addressing Module



SAB801

SAM800

The Sounder Addressing Beacon, SAB801, and Sounder Addressing Module, SAM800, are designed to control an *MX* loop powered sounder base or relay base. The SAB801 has an integral high intensity red beacon that can be separately controlled to illuminate continuously or flash at 1Hz. (There is no facility to synchronise several SAB801 beacons). The SAB801 and SAM800 supply the address decoding in place of a detector, thus providing a remotely controlled sounder when fitted to an 802SB Sounder base or to a remote controlled output when fitted to an 814RB Relay base.

Technical Specifications

	SAB801	SAM800
Operating Voltage		20 to 40Vdc
Quiescent Current		250µA
Alarm Current	3.3mA	250µA ¹
Max. device/Loop ²		200/250
Flash Rate	Cont. or 1Hz	—
Dims (Dia.x H mm)	108 x 32	108 x 22
Weight		70g
Ambient Temp.		-10°C to +55°C
Relative Humidity		10 to 96% (non-cond.)
ActivFire Listing		afp-1446 (pending)
FPANZ Listed	VF/420	VF/656
Part Numbers	516.800.956	516.800.954

1. In addition to associated sounder/relay current. 2. Max. Number of devices between 4BI bases is limited to 40 for AS 1670.1-2004 systems.

850EMT Engineering Management Tool



The 850EMT Engineering Management Tool is a powerful and flexible tool used in the installation, commissioning, diagnostics and servicing of Tyco *MX* detection systems. When used with VIGILANT *MX1* systems, the 850EMT can remotely interrogate, address and test 850 Series detectors via a two-way infrared link. Alternatively *MX* detectors can be plugged on directly. *MX* modules are connected via a programming lead (included). The 850EMT is supplied packaged in a rugged carry case and includes rechargeable batteries, 240V mains adaptor, 12Vdc car adaptor, ancillary programming lead, spare pins for the ancillary lead, and shoulder strap.

Technical Specifications

Operating Voltage	240VAC to 12Vdc Adaptor
Batteries	6x AA NiMH rechargeable
Part Numbers	
850EMTK	Complete Kit
516.800.923	Spare Ancillary Lead
516.800.924	Ancillary Lead Spare Pins

Detector Colour Options



Detectors and bases are supplied white as standard. A range of alternative colours are available, these are supplied as packs of ten detector covers and 4B-C Continuity bases. In addition to the 10 standard shades, any Pantone colour and finish can be supplied as a special order for quantities of 100 or more.

Part Numbers

517.050.501	Sample set of covers and bases - set of 10
517.050.502	Covers and bases in Orange Semi Gloss, pack of 10
517.050.503	Covers and bases in Yellow Gloss, pack of 10
517.050.504	Covers and bases in Matt Green, pack of 10
517.050.505	Covers and bases in Matt Red, pack of 10
517.050.506	Covers and bases in Matt Brown, pack of 10
517.050.507	Covers and bases in Blue Gloss, pack of 10
517.050.508	Covers and bases in Pink Gloss, pack of 10
517.050.509	Covers and bases in Metallic Silver, pack of 10
517.050.510	Covers and bases in Metallic Gold, pack of 10
517.050.511	Covers and bases in Matt Black, pack of 10
517.050.512	Covers and bases Custom colour setup
517.050.513	Covers and bases Custom colour & finish, pack of 10 (minimum order 100)



4B Universal Base



The 4B Universal base is the standard base for use where neither separate short circuit isolation nor loop continuity functionality is required. It is compatible with the 850 Series, 814 Series and 614 Conventional series of detectors.

As with all the 4-inch series bases, the 4B features a detector locking device, LED aperture plug, and temporary park plunger. The temporary park plunger enables a detector to be fitted to the base in a 'park' position - electrically isolated from the terminals.

Technical Specifications

Ambient Temp.	-25°C to +70°C
Relative Humidity	10% to 95% (non-cond)
Dimensions	109 dia x 25H mm
Weight	64g
ActivFire Listed	afp-2927/28/30
Part Number	517.050.041

4B-C Continuity Base



The 4B-C Continuity base is for use with 850 Series detectors to enable the detector's built-in loop isolator. The 4B-C's in-built switch opens when the 850 Series detector is inserted allowing the detector's in-built loop isolator to be in circuit.

When the detector is removed, a spring loaded contact closes to maintain loop continuity.

Technical Specifications

Ambient Temp.	-25°C to +70°C
Relative Humidity	10% to 95% (non-cond)
Dimensions	109 dia x 25H mm
Weight	64g
ActivFire Listed	afp-2927/28/30
Part Number	517.050.042

4B-I Isolator Base



The 4B-I Isolator base is primarily used with detectors that do not have in-built short circuit isolation, such as the 814 Series detectors.

The 850 Series detectors can also be used, however, the detector's in-built short-circuit isolator will not be in operation. The 4B-I includes a yellow LED that lights when the loop is shorted on one side.

Technical Specifications

Operating Voltage	20 to 40Vdc
Quiescent Current	80µA (typ.)
Tripped Current	3.5mA (max.)
Ambient Temp.	-25°C to +70°C
Relative Humidity	10% to 95% (non-cond)
Dimensions	109 dia x 25H mm
Weight	64g
ActivFire Listed	afp-2927/28/30
FPANZ Listed	Pending
Part Number	517.050.043

814RB Relay Base



The 814RB Addressable Relay base provides two sets of changeover volt-free contacts capable of switching 1A (resistive) @ 30Vdc. The relay function is controlled by the MX fire alarm panel via the detector or addressing module plugged into the 814RB. The 814RB may be mounted to the ceiling or plugged into a 4B/5B universal or 4B-I/5B-I isolator base.

Technical Specifications

Quiescent Current	50µA (max.)
Switching Current	1A @ 30Vdc max.
Indoor Applications Only	
Ambient Temp.	-10°C to +55°C
Relative Humidity	10% to 95% (non-cond.)
Dimensions (mm)	110 dia x 38H
ActivFire Listed with MX detectors	
FPANZ Listed	VF/638
Part Number	814RB

802SB Sounder Base



The 802SB Addressable Sounder base provides a sounder function on *MX* addressable systems. Designed for indoor use, it requires an associated detector or addressing module in order to operate, as the sounder base is controlled by the detector/addressing module plugged in. The detector must be locked into the base using the detector locking device. Removal of the detector or loss of power to the loop will cause the sounder to cease sounding. It must be fixed to a flat ceiling or a suitable electrical back box with 50mm fixing centres. It is identified by a white coloured park clip. The 802SB supports ISO8201 T3 tones.

Technical Specification

Operating Voltage	20 to 40Vdc
Quiescent Current	200µA (max.)
Alarm Current	6.8mA (max. volume)
Sound Press. Level	90dBA (max. volume)
Tones	8 Selectable (incl. T3)
Ambient Temp.	-25°C to +70°C
Relative Humidity	10% to 95% (non cond.)
Dimensions (mm)	110 dia x 38H
Devices per loop	50 to 250
ActivFire Listing	afp-1446
Part Number	802SB

4B-DHM Deckhead Mounting



The 4B-DHM Deckhead Mounting can be used with Tyco 850 Series detectors using a 4B base. It provides an IP55 seal between the mounting surface and the detector base for superior environmental protection. The housing has four 20/25mm cable breakouts. The mounting surface should be flat over the area of the underside of the housing to ensure a stable fixing and strong enough to take the weight of the mounting, detector base and detector. Extra Base Accessory Terminals (BATs) are available, one is supplied.


Technical Specifications

Ambient Temp.	-25°C to +70°C
Relative Humidity	10% to 95% (non-cond.)
Dimensions (mm)	115 dia x 42H
Mounting Centres	128.5 mm
Weight	200g
Ingress Protection	IP55

Part Numbers

517.050.051	4B-DHM
517.050.612	BAT Kit - pack of 10

4B-DAF Address Flag



The 850 Series detectors have a feature which automatically transfers the address flags to the detector base when the detector is plugged into the base. On removal of the detector, the flag is retained in the base.

Part Numbers

516.800.915	<i>MX</i> Address Flag (pk 100)
516.800.931	Flag Labels Loop A - Wht
516.800.932	Flag Labels Loop B - Yel
516.800.933	Flag Labels Loop C - Ppl
516.800.934	Flag Labels Loop D - Grn

CTA Ceiling Tile Adaptor (Time-Saver Mount)



The Ceiling Tile Adaptor (CTA) is used to fix detectors to suspended ceilings and allow the detector to be commissioned and tested before the ceiling is fitted. The kit comprises a Bezel, Clamp and Back Box. Using the CTA can reduce installation time by as much as 30%. Where a sounder base is used, an additional adaptor plate must be used.

Technical Specifications

Ambient Temp.	-25 °C to +70 °C
Relative Humidity	10% to 95% (non-cond)
Dimensions (CTA)	165 dia x 51.5H mm
Weight (CTA)	232g

Part Numbers

517.050.060	Ceiling Tile Adaptor Kit (shown) - incl. Back Box, Bezel & Clamp
517.050.056	Back Box (included in kit)
517.050.057	Bezel and Clamp (incl. in kit) (for supply to ceiling installer)
517.050.058	Sounder Base Adaptor Plate (not shown)

4B-EM Euro Adaptor Mount



For surface cable and mini trunking installations, the Euro Adaptor provides a shallow back-box onto which the detector base is fitted.

Technical Specifications

Ambient Temp.	-25 °C to +70 °C
Relative Humidity	10% to 95% (non-cond)
Dimensions	110.5 dia x 20H mm
Weight	70g

Part Number 517.050.052

4B-6A Base 4 inch to 6 inch Adaptor



For use with U.S. style 6 inch electrical back boxes or can be fixed directly to a ceiling and used to conceal marks left when older, large diameter detector bases are replaced with 4-inch bases.

Technical Specifications

Ambient Temp.	-25 °C to +70 °C
Relative Humidity	10% to 95% (non-cond)
Dimensions	151 dia x 16.5H mm
Weight	50g

Part Number 517.050.054

Australia**Tyco Fire Protection Products**

Level 3, 95 Coventry Street

Southbank VIC 3006

Tel : 1300 725 688

Tel : +61 3 9313 9700

Email : tfppcustservice.au@tycofp.com**New Zealand****Tyco Fire Protection Products**

17 Mary Muller Drive

Hillsborough PO Box 19-545

Woolston Christchurch 8241

Tel : +64 9 635 0760

Email : tsp.sales.nz@tycoint.com

Copyright © 2015 Tyco Australia Pty Limited. All rights reserved. Tyco reserves the right to make changes to any aspect of this publication at any time without notice. VIGILANT is a trademark of Tyco New Zealand Limited or its affiliates; *MAX TECHNOLOGY* is a trademark of Thorn Security Limited or its affiliates; TYCO is a trademark of Tyco International Services GmbH.

GEN6DETdatTFPP1502